

# New Force Magnetics, Co.

PO Box 69 Elbert, CO 80106  
Ph. 303-565-3760 Fax 303-565-3762

## Magnetic Receptive Transitional Graphics™ (Change your message fast)

Part Number	Description	Thick	Width	Length	Sq. Ft	Wt.	INK
MRTG1248MW75PVC	Matte White PVC	.012"	48"	75'	300	60 lbs.	1,2,3,4
MRTG1248MW75PPOD	Matte White Outdoor PP	.012"	48"	75'	300	60 lbs.	1,2,3,4
MRTG1248MW75PET	Matte White PET	.012"	48"	75'	300	60 lbs.	1,2,3,4
MRTG1250PETPVCMW75	Matte White PVC/ PET	.012"	50"	75'	312.5	66 lbs.	1,2,3,4
MRTG1250IOAAMW75	Matte White PVC/ Adhesive	.012"	50"	75'	312.5	81 lbs.	1,2,3,4
MRTG1648IOAAMW50	Matte White PVC/ Adhesive	.016"	48"	50'	200	85 lbs.	1,2,3,4
MRTG1648PETPVCMW50	Matte white PET/ PVC	.016"	48"	50'	200	74 lbs.	1,2,3,4
MRTG1250MW75PET	Matte White PET	.012"	50"	75'	312.5	75 lbs.	1,2,3,4
MRTG1250IOAA75	Plain Brown/Adhesive	.014"	50"	75'	312.5	75 lbs.	None
MRTG1648IOAA50	PSA Acrylic Adhesive	.021"	48"	50'	200	76 lbs.	None
MRTG1650IOAA50	PSA Acrylic Adhesive	.021"	50"	50'	208.3	83 lbs.	None
MRTG1648MW50	Matte White PVC	.021"	48"	50'	200	77 lbs.	1,2,3,4
MRTG1648P50	Plain Brown	.021"	48"	50'	200	75 lbs.	None
MRTG754MW100PET	Matte White PET	.007"	54"	100'	450	29 lbs.	1,2,3,4
MRTG760MW100PET	Matte White PET	.007"	60"	100'	500	31 lbs.	1,2,3,4

Suggested inks: 1 = Solvent, 2 = Eco-Solvent, 3 = UV low heat, 4 = Latex low heat, 5 = Dye ink, and then coated.

Distributor and Customer are responsible for testing inks prior to purchasing and printing.

TT = Total Thickness, Length = Roll Length, Sq. Ft. = per roll, Wt. = Approximate Weight.

### Receptive Strength

Ferrous Sheet thickness	Magnet sheet thickness	Magnetic Receptive pull force g/cm2	Magnetic Receptive pull force pound/square feet
.007"	.030"		
	.020"		
	.015"		

.012"	.030"	11	23
	.020"	7	14
	.015"	3	6

.016"	.030"	17	35
	.020"	11	23
	.015"	4	8